

Datum: 29.04.2025



(slika je simbolična)

Hitre spojke I.D. 7.8visok pretok,Fi 8

Kategorija: [Quick disconnect coupling DN 7.8, with hose stem](#)

Šifra: **107413RIE**

Kratek opis

Quick-connect coupling I.D. 7.8, High flow rate, Sleeve I.D. 8, Operating pressure 0 - 35 bar, Medium/ambient temp. -20°C to 40°C

One-hand quick disconnect couplings, one side sealing, that combine high flow rates (approx. twice as high as the popular DN 7.2 standard coupling) with minimal coupling forces.

Suitable for all applications with an above-average air requirement!

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

These quick disconnect couplings are not suitable for direct attachment to pulsating tools.

We recommend using our vibration dampers, according to ISO 6150 § 7.1.

Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive, food technology, aerospace.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Krogla	Stainless steel at 6 bar and $\Delta p = 0.5$ bar
Merjenje pretoka	Nickel-plated brass
Navojni kos	I.D. 8
Povezava	Stainless steel
Pritrdilni obroč	Brass
Sedež ventila	Extremely robust, ergonomic plastic
Sprostitutveni rokav	Steel, QPQ treated
Telo ventila	NBR
Tesnilo	Brass
Ventil	Stainless steel
Vzmet	7.8
DN	19
a/f [mm]	35
Max. obratovalni tlak [bar]	40
Max. sobna temperatura [°C]	40
Max. temperatura medija [°C]	80.0
Dolžina [mm]	2100 l/min (air)
Pretok	