

Datum: 30.04.2025



(slika je simbolična)

## Hitre spojke I.D. 5 »connect line« cev 8x6

Kategorija: [Quick disconnect coupling DN 5 with hose connector](#)Šifra: **115643RIE**

### Kratek opis

Quick-connect coupling I.D. 5 »connect line«, nickel-plated brass, Hose 8x6, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C

"

Low-priced, one-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop.

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

Areas of application: Pneumatic system, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology.

"

### Tehnične Specifikacije

|                              |                                                              |
|------------------------------|--------------------------------------------------------------|
| Min. sobna temperatura [°C]  | -20                                                          |
| Min. temperatura medija [°C] | -20                                                          |
| Delovni tlak                 | 0 to 35 bar, maximum static working pressure (non-pulsating) |
| Merjenje pretoka             | at 6 bar and $\Delta p = 0.5$ bar                            |
| Ohišje                       | Nickel-plated brass                                          |
| Povezava                     | Hose connection 8x6                                          |
| Pritrdilni obroč             | Stainless steel                                              |
| Rokav                        | Nickel-plated brass                                          |
| Telo ventila                 | Nickel-plated brass                                          |
| Tesnilo                      | NBR                                                          |
| Vzmet                        | Stainless steel                                              |
| Zaporni zatič                | Stainless steel                                              |
| DN                           | 5                                                            |
| a/f [mm]                     | 14                                                           |
| Dolžina [mm]                 | 42.4                                                         |
| Max. sobna temperatura [°C]  | 100                                                          |
| Max. temperatura medija [°C] | 100                                                          |
| Pretok                       | 560 l/min (air)                                              |