

**Datum:** 29.04.2025

(slika je simbolična)

## **Hitre spojke s prekrN.N.o matico I.D. 2.7iz med. cev 4x3**

Kategorija: [Quick disconnect coupling DN 2.7, hose connector](#)Šifra: **107075RIE**

### **Kratek opis**

Quick-connect coupling I.D. 2.7, bright brass, Hose connection 4x3, Operating pressure 0-35 bar, Med./ambient temp. -20°C to 100°C

One-hand quick disconnect couplings, one side sealing, extremely compact with a large bore and only a small pressure drop.

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive.

### **Tehnične Specifikacije**

|                              |                                                              |
|------------------------------|--------------------------------------------------------------|
| Min. sobna temperatura [°C]  | -20                                                          |
| Min. temperatura medija [°C] | -20                                                          |
| Delovni tlak                 | 0 to 35 bar, maximum static working pressure (non-pulsating) |
| Krogla                       | Stainless steel                                              |
| Merjenje pretoka             | at 6 bar and $\Delta p = 0.5$ bar                            |
| Ohišje                       | Brass with a bare metal surface                              |
| Povezava                     | Hose connection 4x3                                          |
| Pritrdilni obroč             | Stainless steel                                              |
| Rokav                        | Brass with a bare metal surface                              |
| Telo ventila                 | Brass with a bare metal surface                              |
| Tesnilo                      | NBR                                                          |
| Vzmet                        | Stainless steel                                              |
| DN                           | 2.7                                                          |
| Dolžina [mm]                 | 34.0                                                         |
| Max. sobna temperatura [°C]  | 100                                                          |
| Max. temperatura medija [°C] | 100                                                          |
| Pretok                       | 165 l/min (air)                                              |