

Datum: 29.04.2025



(slika je simbolična)

## Hitre spojke z N.N. I.D. 2.7iz med.G 1/8 N.N.

Kategorija: [Quick disconnect coupling DN 2.7, female](#)

Šifra: **107072RIE**

### Kratek opis

Quick-connect coupling I.D. 2.7, bright brass, G 1/8 IT,  
Operating pressure 0 - 35 bar, Med. / ambient temp. -20°C  
to 100°C

"  
One-hand quick disconnect couplings, one side sealing,  
extremely compact with a large bore and only a small  
pressure drop.  
To prevent injuries or a "whiplash" effect, we recommend  
that the plug-in nipple is held with one hand during  
uncoupling.

Areas of application: Pneumatic system, machine and plant  
engineering, measurement, monitoring and control systems,  
manufacturing industry, medical technology, chemical /  
pharmaceutical industry, automotive.

"

### Tehnične Specifikacije

|                                 |                                                                    |
|---------------------------------|--------------------------------------------------------------------|
| Min. sobna<br>temperatura [°C]  | -20                                                                |
| Min. temperatura<br>medija [°C] | -20                                                                |
| Delovni tlak                    | 0 to 35 bar, maximum<br>static working pressure<br>(non-pulsating) |
| Krogla                          | Stainless steel                                                    |
| Merjenje pretoka                | at 6 bar and $\Delta p = 0.5$ bar                                  |
| Ohišje                          | Brass with a bare metal<br>surface                                 |
| Povezava                        | G 1/8 IT                                                           |
| Pritrdilni obroč                | Stainless steel                                                    |
| Rokav                           | Brass with a bare metal<br>surface                                 |
| Telo ventila                    | Brass with a bare metal<br>surface                                 |
| Tesnilo                         | NBR                                                                |
| Vzmet                           | Stainless steel                                                    |
| DN                              | 2.7                                                                |
| a/f [mm]                        | 12                                                                 |
| Dolžina [mm]                    | 28.0                                                               |
| Max. sobna<br>temperatura [°C]  | 100                                                                |
| Max. temperatura<br>medija [°C] | 100                                                                |
| Pretok                          | 165 l/min (air)                                                    |