

Datum: 01.05.2025



(slika je simbolična)

## Kaljeni cevni vtikač DN 9, zunanji navoj, G 3/8, dolžina 17

Kategorija: [Push-in plug DN 9, without shut-off valve, ET](#)

Šifra: **107979RIE**

### Kratek opis

Tempered plug-in nipple DN 9, Exterior thread, nickel-plated brass, G 3/8, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C

Compatible with HASCO Z 8 system.

For temperature control applications involving hot or cold water or heat transfer oil.

Optionally with free passage, one or both sides sealing.

Female-threaded couplings and plugs with female-threaded PTFE seal.

### Tehnične Specifikacije

|                              |                         |
|------------------------------|-------------------------|
| Min. sobna temperatura [°C]  | -20                     |
| Min. temperatura medija [°C] | -20                     |
| Krogla                       | Stainless steel         |
| Material                     | Nickel-plated brass     |
| Navoj                        | G 3/8                   |
| Pritrdilni obroč             | Stainless steel         |
| Srednje                      | Air, water, oil, vacuum |
| Tesnilo                      | FPM (PTFE coated)       |
| Vzmet                        | Stainless steel         |
| Max. obratovalni tlak [bar]  | 15                      |
| a/f [mm]                     | 17                      |
| Dolžina [mm]                 | 26.0                    |
| Max. sobna temperatura [°C]  | 160                     |
| Max. temperatura medija [°C] | 160                     |