

Datum: 01.05.2025



(slika je simbolična)

## Kaljeni vtični konektor DN 6Z.N.z zapornim ventilomG 1/4

Kategorija: [Push-in plug DN 6, with shut-off valve, ET](#)

Šifra: **107937RIE**

### Kratek opis

Tempered plug-in nipple DN 6, with blocking valve, ET, nickel-plated brass, G 1/4, Operating pressure max. 15 bar  
Compatible with HASCO Z 8 system.  
For temperature control applications involving hot or cold water or heat transfer oil, e.g. for cooling circuits on plastics processing machines.  
Optionally with free passage, one or both sides sealing.  
Female-threaded couplings and plugs with female-threaded PTFE seal.

### Tehnične Specifikacije

|                              |                         |
|------------------------------|-------------------------|
| Min. sobna temperatura [°C]  | -20                     |
| Min. temperatura medija [°C] | -20                     |
| Krogla                       | Stainless steel         |
| Material                     | Nickel-plated brass     |
| Navoj                        | G 1/4                   |
| Pritrdilni obroč             | Stainless steel         |
| Srednje                      | Air, water, oil, vacuum |
| Tesnilo                      | FPM (PTFE coated)       |
| Vzmet                        | Stainless steel         |
| a/f [mm]                     | 15                      |
| Max. obratovalni tlak [bar]  | 15                      |
| Dolžina [mm]                 | 29.0                    |
| Max. sobna temperatura [°C]  | 160                     |
| Max. temperatura medija [°C] | 160                     |