

Datum: 16.12.2025



(slika je simbolična)

Komp. cilind. del. v dveh smereh, bat Ø 12, hod 15, M5, ISO21287

Kategorija: [Compact cylinders double-acting, female piston rod](#)

Šifra: **155322RIE**

Kratek opis

Compact cyl.ISO 21287, double-acting, female piston rod, magnet, PistonØ12, Stroke15, M5, Work.press.max.10bar, Temp.-20°C to 70°C
Series acc. to ISO 21287 characterised by a very short and compact design.
The standard type features a magnetic piston.
Piston rod optionally with male or female thread.
Suitable for filtered, unlubricated or lubricated compressed air.
If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium S45C steel, hard chrome-plated
Batnica	M3x0.5
Batnica IT	double-acting
Ffunkcija	female piston rod
Gewinde Kolbenstange	with magnet
Magnet	Anodised aluminium jacket with T-slots
Ovoj	M5
Povezava	ACE series
Serijska	acc. to ISO 21287
Standard	NBR
Tesnilo	
Max. delovni tlak [bar]	10
Bat Ø [mm]	12
Stroke [mm]	15
Max. temperaturno območje [°C]	70