

Datum: 01.05.2025



(slika je simbolična)

## Komp. cilind. del. v dveh smereh, bat Ø 16hod 35M5x0,8

Kategorija: [Compact cylinder, double-acting, with magnet](#)

Šifra: **115279RIE**

### Kratek opis

Compact cylinder »ACP«, double-acting, Piston Ø 16, Stroke 35, Connection M5x0,8, Working pressure 1-10 bar, Temp. -20 °C to 70 °C

Characterised by a very short and compact design.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

### Tehnične Specifikacije

|                                |                   |
|--------------------------------|-------------------|
| Min. temperaturno območje [°C] | -20               |
| Bat                            | Aluminium         |
| Batnica                        | Steel             |
| Batnica IT                     | M4x0.7            |
| Ffunkcija                      | double-acting     |
| Gewinde Kolbenstange           | female piston rod |
| Magnet                         | with magnet       |
| Ovoj                           | Aluminium         |
| Povezava                       | M5x0.8            |
| Serijska                       | ACP series        |
| Tesnilo                        | NBR               |
| Min. delovni tlak [bar]        | 1                 |
| Batnica Ø [mm]                 | 8                 |
| Max. delovni tlak [bar]        | 10                |
| Bat Ø [mm]                     | 16                |
| Stroke [mm]                    | 35                |
| Max. temperaturno območje [°C] | 70                |