

Datum: 30.04.2025



(slika je simbolična)

## Komp. cilind. del. v dveh smereh, bat Ø 25hod 50M5x0,8

Kategorija: [Compact cylinder, double-acting, with magnet](#)

Šifra: **115310RIE**

### Kratek opis

Compact cylinder »ACP«, double-acting, Piston Ø 25, Stroke 50, Connection M5x0,8, Working pressure 1-10 bar, Temp. -20 °C to 70 °C

Characterised by a very short and compact design.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

### Tehnične Specifikacije

|                                |                        |
|--------------------------------|------------------------|
| Min. temperaturno območje [°C] | -20                    |
| Bat                            | Aluminium              |
| Batnica                        | Stainless steel 1.1191 |
| Batnica IT                     | M5x0.8                 |
| Ffunkcija                      | double-acting          |
| Gewinde Kolbenstange           | female piston rod      |
| Magnet                         | with magnet            |
| Ovoj                           | Aluminium              |
| Povezava                       | M5x0.8                 |
| Serijska                       | ACP series             |
| Tesnilo                        | NBR                    |
| Min. delovni tlak [bar]        | 1                      |
| Batnica Ø [mm]                 | 10                     |
| Max. delovni tlak [bar]        | 10                     |
| Bat Ø [mm]                     | 25                     |
| Stroke [mm]                    | 50                     |
| Max. temperaturno območje [°C] | 70                     |