

Datum: 16.12.2025



(slika je simbolična)

## Komp. cilind. del. v dveh smereh, bat Ø 40hod 40G 1/8

Kategorija: [Compact cylinders double-acting, female piston rod](#)

Šifra: **106001RIE**

### Kratek opis

Compact cylinder LINER, ISO 21287, double-acting, Piston Ø 40, Stroke 40, G 1/8, Working pressure max. 10 bar, Temp. -10°C to 60°C

New series acc. to ISO 21287 characterised by a very short and compact design.

The standard type features a magnetic piston.

Piston rod optionally with male or female thread.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

### Tehnične Specifikacije

|                                |                                        |
|--------------------------------|----------------------------------------|
| Min. temperaturno območje [°C] | -10                                    |
| Bat                            | POM                                    |
| Batnica                        | C45 steel, hard chrome-plated          |
| Batnica IT                     | M8                                     |
| Ffunkcija                      | double-acting                          |
| Gewinde Kolbenstange           | female piston rod with magnet          |
| Magnet                         | Anodised aluminium jacket with T-slots |
| Ovoj                           | G 1/8                                  |
| Povezava                       | LINER series                           |
| Serijska                       | acc. to ISO 21287                      |
| Standard                       | NBR                                    |
| Tesnilo                        | 0.4                                    |
| Min. nastavljeni tlak [bar]    | 10                                     |
| Max. delovni tlak [bar]        | 40                                     |
| Bat Ø [mm]                     | 40                                     |
| Stroke [mm]                    | 40                                     |
| Max. temperaturno območje [°C] | 60                                     |