

Datum: 16.12.2025



(slika je simbolična)

## Komp. cilind.del. v dveh smereh,bat Ø125,hod25,G1/4,ISO21287

Kategorija: [Compact cylinders double-acting, male piston rod](#)  
Šifra: **155788RIE**

### Kratek opis

Compact cyl.ISO 21287, double-acting, male piston rod  
magnet, PistonØ125, Stroke25, G1/4,  
Work.press.max.10bar, Temp.-20°C to 70°C  
Series acc. to ISO 21287 characterised by a very short and  
compact design.  
The standard type features a magnetic piston.  
Piston rod optionally with male or female thread.  
Suitable for filtered, unlubricated or lubricated compressed  
air.  
If lubrication is used, it must be continuous.

### Tehnične Specifikacije

|                                |                                        |
|--------------------------------|----------------------------------------|
| Min. temperaturno območje [°C] | -20                                    |
| Bat                            | Aluminium                              |
| Batnica                        | S45C steel, hard chrome-plated         |
| ET batnice                     | M20x1.5                                |
| Ffunkcija                      | double-acting                          |
| Gewinde Kolbenstange           | male piston rod                        |
| Magnet                         | with magnet                            |
| Ovoj                           | Anodised aluminium jacket with T-slots |
| Povezava                       | G 1/4                                  |
| Serijska                       | ACE series                             |
| Standard                       | acc. to ISO 21287                      |
| Tesnilo                        | NBR                                    |
| Max. delovni tlak [bar]        | 10                                     |
| Stroke [mm]                    | 25                                     |
| Max. temperaturno območje [°C] | 70                                     |
| Bat Ø [mm]                     | 125                                    |