

Datum: 15.12.2025



(slika je simbolična)

komp. cilinder LINERdelujoč v dveh smerehbat Ø 25hod 10M5

Kategorija: [Compact cylinders double-acting, male piston rod](#)
Šifra: **106055RIE**

Kratek opis

Compact cylinder LINER, ISO 21287, double-acting, Piston Ø 25, Stroke 10, M5, Working pressure max. 10 bar, Temp. -10°C to 60 °C

New series acc. to ISO 21287 characterised by a very short and compact design.

The standard type features a magnetic piston.

Piston rod optionally with male or female thread.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Bat	POM
Batnica	C45 steel, hard chrome-plated
ET batnice	M8
Ffunkcija	double-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Ovoj	Anodised aluminium jacket with T-slots
Povezava	M5
Serijska	LINER series
Standard	acc. to ISO 21287
Tesnilo	NBR
Min. nastavljeni tlak [bar]	0.6
Max. delovni tlak [bar]	10
Stroke [mm]	10
Bat Ø [mm]	25
Max. temperaturno območje [°C]	60