

Datum: 15.12.2025



(slika je
simbolična)

komp.cilinder,enosmerni,zunanjiP-Ø32, hod 10, G1/8, ISO21287

Kategorija: [Compact cylinders, single-acting, extended, female](#)

Šifra: **155924RIE**

Kratek opis

Compact cyl.ISO 21287,single-acting,female piston rod,
ext.,magnet,PistonØ32,Stroke10,G1/8,Work.press.max.10ba
r,Temp.-20°C to 70°C

Series acc. to ISO 21287 characterised by a very short and
compact design.

The standard type features a magnetic piston.

Piston rod optionally with male or female thread.

Suitable for filtered, unlubricated or lubricated compressed
air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	S45C steel, hard chrome- plated
Batnica IT	M8x1.25
Ffunkcija	single-acting
Gewinde Kolbenstange	female piston rod
Magnet	with magnet
Ovoj	Anodised aluminium
Povezava	jacket with T-slots
Serijska	G 1/8
Standard	ATE series
Starting position	acc. to ISO 21287
Tesnilo	pressureless in the extended position
Max. delovni tlak [bar]	NBR
Stroke [mm]	10
Bat Ø [mm]	10
Max. temperaturno območje [°C]	32
	70