

Datum: 01.05.2025

(slika je
simbolična)

[komp.cilinder,enosmerni,zunanjibat Ø20, hod 25, M5, ISO21287](#)

Kategorija: [Compact cylinders, single-acting, extended, female](#)Šifra: **155917RIE**

Kratek opis

Compact cyl.ISO 21287, single-acting, female piston rod, ext.,magnet,PistonØ20,Stroke25,M5,Work.press.max.10bar, Temp.-20°C to 70°C

Series acc. to ISO 21287 characterised by a very short and compact design.

The standard type features a magnetic piston.

Piston rod optionally with male or female thread.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium S45C steel, hard chrome-plated
Batnica	M6x1.0
Batnica IT	single-acting
Ffunkcija	female piston rod with magnet
Gewinde Kolbenstange	Anodised aluminium jacket with T-slots
Magnet	M5
Ovoj	ATE series
Povezava	acc. to ISO 21287
Serijski Standard	pressureless in the extended position
Starting position	NBR
Tesnilo	NBR
Max. delovni tlak [bar]	10
Bat Ø [mm]	20
Stroke [mm]	25
Max. temperaturno območje [°C]	70