

Datum: 30.04.2025



(slika je simbolična)

## Kot. pregrad. navoj. prik., M16x1.5, za 8/10 mm, AF 22, PA

Kategorija: [Bulkhead elbow couplings - polyamide](#)

Šifra: **110846RIE**

### Kratek opis

Angled bulkhead connector, M16x1.5, for hose 8/10 mm, AF 22, Working pressure max. 10 bar (20 °C)/max. 1 bar (60 °C), PA

Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzine, diesel oil, fuel oil and alkalis. Not suitable for use with acids.

### Tehnične Specifikacije

|                                    |                    |
|------------------------------------|--------------------|
| Narezana matica                    | Polypropylene (PP) |
| Navoj                              | M16x1.5            |
| Telo vijačnega priključka          | Polyamide (PA)     |
| Vpenjalni obroč                    | Polypropylene (PP) |
| Max. delovni tlak pri 60 ° C [bar] | 1                  |
| Za cevi [mm]                       | 8/10               |
| Max. delovni tlak pri 20 ° C [bar] | 10                 |
| a/f [mm]                           | 22                 |
| L2 [mm]                            | 36.0               |
| L1 [mm]                            | 58.0               |