

Datum: 29.04.2025



(slika je simbolična)

Kot. varnos. ventil, za tekoč., G 1 1/4, vkl. prit. 7 bar

Kategorija: [Angle-tip Varnostni ventil G 1 1/4](#)

Šifra: **105621RIE**

Kratek opis

Corner safety valve, for liquids, Red brass, NBR, Operating temp. -10 °C to 110 °C, G 1 1/4, AF 50, Trigger pressure 7 bar

For non-toxic, non-flammable liquids.

No evaporation allowed when blowing off.

With diaphragm to protect the spring and with lifting device.

Type-tested, TÜV-SV. 749. F

Tehnične Specifikacije

Min. delovna temperatura [°C]	-10
Membrane	NBR
Navoj	G 1 1/4
Notranji deli	Brass
Ohišje	Bronze
Vstop in izstop	Each with female thread type G acc. to DIN EN ISO 228-1
Vzmet	C steel
Vzmet pokrova motorja	Brass
Min. prilagoditveno območje [bar]	1
Min. nastavljeni tlak [bar]	7
Max. območje nastavitve [bar]	10
L2 [mm]	35.0
L1 [mm]	40.0
a/f [mm]	50
Max. delovna temperatura [°C]	110
H [mm]	152.0