

Datum: 16.12.2025



(slika je simbolična)

krog. ventil med., El. vklop 230 V AC, 50 Hz, 3/4

Kategorija: [Brass ball valve, electric actuator 230 VAC, 50 Hz](#)

Šifra: **103695RIE**

Kratek opis

Brass ball valve, Electr. actuation drive, 230 V AC, 50 Hz,
Operating temperature -20 °C to 70 °C, Rp 3/4, DN 20, PN
max. 40 bar

Voltage range 230 VAC, 50 Hz or 24 VDC.

2-way cock, full bore, for neutral gases and liquids.

Reversible electric rotary actuator.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-30
Min. delovna temperatura [°C]	-20
Gred izbirnika	Hard chrome-plated brass
Indikator položaja	Manually operated
IP zaščita	IP 68
Krogelno tesnilo	PTFE, glass fibre- reinforced
Krogla	Hard chrome-plated brass
Material	Nickel-plated brass
Montažna prirobnica	ISO 5211
Navoj	Rp 3/4
Ohišje	Aluminium powder- coated
Tesnilo gredi izbirnika	FKM
Čas aktivacije [sec.]	15
D [mm]	20.0
DN	20
Delovni cikel [%]	30
Relativna vlažnost	30 % to 95 %
a/f [mm]	32
PN [bar]	40
Max. delovna temperatura [°C]	70
Max. sobna temperatura [°C]	70
L [mm]	80.0
A [mm]	153.0
B [mm]	167.0
Napetost	230 VAC, 50 Hz