

Datum: 30.04.2025



(slika je simbolična)

## krog. ventil med., pnevm. vklop vzmetni preklop, 3/4

Kategorija: [Brass ball valve, single-acting actuator](#)

Šifra: **103533RIE**

### Kratek opis

2-way brass ball valve, Pneumat. actuation drive spring switching, Operating temp. max. 70 °C, Rp 3/4, DN 20, PN max. 40 bar

2-way cock, full bore.

Pneumatic actuators, double- or single acting version and integrated end-position feedback.

### Tehnične Specifikacije

|                                   |                                            |
|-----------------------------------|--------------------------------------------|
| Min. delovna temperatura [°C]     | -20                                        |
| Adapter ventila                   | Supplied as standard                       |
| Material krogelnega ventila       | Nickel-plated brass, with ISO flange plate |
| Navoj                             | Rp 3/4                                     |
| Pogonski material                 | Anodised aluminium                         |
| Premaz za krogelni ventil         | PTFE / FKM                                 |
| Premaz za pogon                   | NBR                                        |
| Različica                         | single-acting - spring to close            |
| Priporočeni vodeni tlak [bar]     | 5.5                                        |
| Max. vodeni tlak aktuatorja [bar] | 10                                         |
| D [mm]                            | 20.0                                       |
| DN                                | 20                                         |
| a/f [mm]                          | 32                                         |
| PN [bar]                          | 40                                         |
| Max. delovna temperatura [°C]     | 70                                         |
| L [mm]                            | 80.0                                       |
| Kot vrtenja [°]                   | 90                                         |
| A [mm]                            | 133.0                                      |
| B [mm]                            | 145.0                                      |