

Datum: 15.12.2025



(slika je simbolična)

krog. ventil robustnejša oblika, metuljasta ročica, ET/ET, R 1/2

Kategorija: [Ball valve with butterfly handle, ET/ET](#)
Šifra: **103299RIE**

Kratek opis

Ball valve heavy duty design, Butterfly handle, ET/ET, nickel-plated brass, Operating temp. -20°C to 130°C, R 1/2, PN max. 100 bar

Applications: Compressed air, water, neutral and non-toxic gases, fuel oil (light distillate), fuel oil (heavy), lubricating oils, diesel oils.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Material navojev	Brass with a bare metal surface
Navoj	R 1/2
Ohišje	Nickel-plated brass
Ročica - metuljček	Aluminium, painted black
Standardni navoj	R thread acc. to DIN EN 10226 (ISO 7-1)
Stebelno tesnilo	PTFE
E [mm]	14.9
F [mm]	14.9
DN	15
a/f [mm]	27
B [mm]	54.5
A [mm]	55.0
L [mm]	82.0
PN [bar]	100
Max. delovna temperatura [°C]	130