

Datum: 15.12.2025



(slika je simbolična)

krog. ventil robustnejša oblika, metuljasta ročica, IT/ET, G/R 1

Kategorija: [Ball valve with butterfly handle, IT/ET](#)

Šifra: **103296RIE**

Kratek opis

Ball valve heavy duty design, Butterfly handle, IT/ET, nickel-plated brass, Operating temp. -20°C to 130°C, G/R 1, PN max. 80 bar

Applications: Compressed air, water, neutral and non-toxic gases, fuel oil (light distillate), fuel oil (heavy), lubricating oils, diesel oils.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Material navojev	Brass with a bare metal surface
Navoj	G/R 1
Ohišje	Nickel-plated brass
Ročica - metuljček	Aluminium, painted black
Standardni navoj	G thread DIN EN ISO 228-1, R thread DIN EN 10226 (ISO 7-1)
Stebelno tesnilo	PTFE
F [mm]	14.5
E [mm]	19.0
DN	25
a/f 2 [mm]	39
a/f 1 [mm]	40
A [mm]	70.0
B [mm]	70.5
PN [bar]	80
L [mm]	88.4
Max. delovna temperatura [°C]	130