

Datum: 01.05.2025



(slika je simbolična)

## krog. ventil standar.obilka, črna jekl. ročica, IT/ET, G 3/4

Kategorija: [Ball valve with black steel lever, IT/ET](#)

Šifra: **103198RIE**

### Kratek opis

Ball valve standard design, black steel lever, IT/ET, nickel-plated brass, Operating temp. -15 °C to 90 °C, G 3/4, PN max. 40 bar

Applications: Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture.

### Tehnične Specifikacije

|                               |                                                             |
|-------------------------------|-------------------------------------------------------------|
| Min. delovna temperatura [°C] | -15                                                         |
| Krogelno tesnilo              | PTFE                                                        |
| Krogla                        | Chrome-plated brass                                         |
| Material                      | Nickel-plated brass                                         |
| Material navojev              | Brass with a bare metal surface                             |
| Navoj                         | G 3/4                                                       |
| Ročica                        | Steel, with plastic coating                                 |
| Standardni navoj              | G thread acc. to DIN EN ISO 228-1                           |
| Stebelno tesnilo              | 2 O-rings HNBR/EPDM peroxide crosslinked, sealing ring PTFE |
| E [mm]                        | 10.5                                                        |
| F [mm]                        | 10.5                                                        |
| DN                            | 20                                                          |
| PN [bar]                      | 40                                                          |
| B [mm]                        | 48.4                                                        |
| L [mm]                        | 69.5                                                        |
| Max. delovna temperatura [°C] | 90                                                          |
| A [mm]                        | 105.0                                                       |