

Datum: 16.12.2025



(slika je simbolična)

Krogelni ventil 3/2 »FUTURA«, zaklepni, Velikost 2, G 1/2

Kategorija: [Ball valves](#)

Šifra: **100286RIE**

Kratek opis

Ball valve 3/2-way »FUTURA«, lockable, Size 2, G 1/2,
Exhaust G 1/2, Input pressure max. 16 bar, Temperature -10
°C to 50 °C

Lockable ball valve, 3/2-way type including silencer,
mechanically operated.

Rotary switch can be turned 90°, with indication of
positions:

Horizontal: Input closed - outlet exhausted

Vertical: Flow open - exhaust closed

Exhaust air can be collected.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Izpušni zrak	G 1/2 At $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Merjenje pretoka	
Navoj	G 1/2
Ohišje	PA66 GF60
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Velikost	2
Max. vhodni tlak [bar]	16
Max. temperaturno območje [°C]	50
A [mm]	63.0
C [mm]	70.5
B [mm]	127.0
Pretok [l/min]	14000