

Datum: 01.05.2025



(slika je simbolična)

krogelni ventil EN 331 DVGW, Ročica, nikljana medenina, Rp 1 1/4

Kategorija: [Ball valves acc. to EN 331 with DIN DVGW](#)
Šifra: **103307RIE**

Kratek opis

Ball valve EN 331 DVGW, Hand lever, IT/IT, nickel-plated brass, Operating temp. -20°C to 60°C, Rp 1 1/4, DN 32, PN max 5 bar (gas)
Ball valves with full bore, for gas installations.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Delovni tlak	max. 5 bar (MOP 5) for gas installations acc. to DVGW
DVGW odobritev	DIN EN 331:2013-05
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass (CW617N)
Material navojev	Brass
Navoj	Rp 1 1/4
Ohišje	Nickel-plated brass
Ročica	Steel, painted yellow
Standardni navoj	Thread acc. to ISO 7-1
Stebelno tesnilo	NBR / FKM
E [mm]	21.4
DN	32
a/f [mm]	47
Max. delovna temperatura [°C]	60
B [mm]	75.0
L [mm]	99.5
A [mm]	138.0