

Datum: 29.04.2025



(slika je simbolična)

## krogelni ventil EN 331, DVGW, Ročica, nikljana medenina, Rp 3/4

Kategorija: [Ball valves acc. to EN 331 with DIN DVGW](#)  
Šifra: **103305RIE**

### Kratek opis

Ball valve EN 331, DVGW, Hand lever, IT/IT, nickel-plated brass, Operating temp. -20°C to 60°C, Rp 3/4, DN 20, PN max. 5 bar (gas)  
Ball valves with full bore, for gas installations.

### Tehnične Specifikacije

|                               |                                                       |
|-------------------------------|-------------------------------------------------------|
| Min. delovna temperatura [°C] | -20                                                   |
| Delovni tlak                  | max. 5 bar (MOP 5) for gas installations acc. to DVGW |
| DVGW odobritev                | DIN EN 331:2013-05                                    |
| Krogelno tesnilo              | PTFE                                                  |
| Krogla                        | Chrome-plated brass (CW617N)                          |
| Material navojev              | Brass                                                 |
| Navoj                         | Rp 3/4                                                |
| Ohišje                        | Nickel-plated brass                                   |
| Ročica                        | Steel, painted yellow                                 |
| Standardni navoj              | Thread acc. to ISO 7-1                                |
| Stebelno tesnilo              | NBR / FKM                                             |
| E [mm]                        | 16.3                                                  |
| DN                            | 20                                                    |
| a/f [mm]                      | 31                                                    |
| B [mm]                        | 54.8                                                  |
| Max. delovna temperatura [°C] | 60                                                    |
| L [mm]                        | 68.0                                                  |
| A [mm]                        | 113.0                                                 |