

Datum: 30.04.2025



(slika je simbolična)

## krogelni ventil medenina, električni vklop, 24 V DC, Rp 1 1/2

Kategorija: [Brass ball valve with electric actuator 24 VDC](#)

Šifra: **103704RIE**

### Kratek opis

Brass ball valve, Electrical actuation drive, 24 V DC,  
Operating temperature -20 °C to 70 °C, Rp 1 1/2, DN 40, PN  
max. 25 bar  
Voltage range 230 VAC, 50 Hz or 24 VDC.  
2-way cock, full bore, for neutral gases and liquids.  
Reversible electric rotary actuator.

### Tehnične Specifikacije

|                               |                              |
|-------------------------------|------------------------------|
| Min. sobna temperatura [°C]   | -30                          |
| Min. delovna temperatura [°C] | -20                          |
| Gred izbirnika                | Hard chrome-plated brass     |
| Indikator položaja            | Manually operated            |
| IP zaščita                    | IP 68                        |
| Krogelno tesnilo              | PTFE, glass fibre-reinforced |
| Krogla                        | Hard chrome-plated brass     |
| Material                      | Nickel-plated brass          |
| Montažna prirobnica           | ISO 5211                     |
| Navoj                         | Rp 1 1/2                     |
| Ohišje                        | Aluminium powder-coated      |
| Tesnilo gredi izbirnika       | FKM                          |
| Čas aktivacije [sec.]         | 20                           |
| Napetost                      | 24 VDC                       |
| PN [bar]                      | 25                           |
| Delovni cikel [%]             | 30                           |
| Relativna vlažnost            | 30 % to 95 %                 |
| D [mm]                        | 36.0                         |
| DN                            | 40                           |
| a/f [mm]                      | 55                           |
| Max. delovna temperatura [°C] | 70                           |
| Max. sobna temperatura [°C]   | 70                           |
| L [mm]                        | 120.0                        |
| A [mm]                        | 153.0                        |
| B [mm]                        | 188.0                        |