

Datum: 16.12.2025



(slika je simbolična)

## [krogelni ventil medenina, pnevmatski vklop duple-acting, Rp 1](#)

Kategorija: [Brass ball valves, double-acting actuator](#)

Šifra: **103525RIE**

### Kratek opis

2-way brass ball valve, Pneumat. actuation drive double-acting, Operating temperature max. 70 °C, Rp 1, DN 25, PN max. 40 bar

2-way cock, full bore.

Pneumatic actuators, double- or single acting version and integrated end-position feedback.

### Tehnične Specifikacije

|                                   |                                            |
|-----------------------------------|--------------------------------------------|
| Min. delovna temperatura [°C]     | -20                                        |
| Adapter ventila                   | Supplied as standard                       |
| Material krogelnega ventila       | Nickel-plated brass, with ISO flange plate |
| Navoj                             | Rp 1                                       |
| Pogonski material                 | Anodised aluminium                         |
| Premaz za krogelni ventil         | PTFE / FKM                                 |
| Premaz za pogon                   | NBR                                        |
| Različica                         | double-acting                              |
| Priporočeni vodeni tlak [bar]     | 5.5                                        |
| Max. vodeni tlak aktuatorja [bar] | 10                                         |
| D [mm]                            | 25.0                                       |
| DN                                | 25                                         |
| PN [bar]                          | 40                                         |
| a/f [mm]                          | 41                                         |
| Max. delovna temperatura [°C]     | 70                                         |
| Kot vrtenja [°]                   | 90                                         |
| L [mm]                            | 90.0                                       |
| A [mm]                            | 133.0                                      |
| B [mm]                            | 148.0                                      |