

Datum: 15.12.2025



(slika je simbolična)

krogelni ventil nerjavno jeklo, Pneumat. vklop, Rp 1

Kategorija: [Stainless steel ball valve, double-acting actuator](#)Šifra: **103599RIE**

Kratek opis

2-way stainless steel ball valve, Pneumat. actuation drive, double-acting, Operating temp. -20 °C to 70 °C, Rp 1, PN max. 63 bar

2-way cock, 3-piece, full bore.

Pneumatic actuators, double- or single acting version and integrated end-position feedback.

Standardised interfaces:

Actuator/valve interface: Four or eight female threads in the actuator housing acc. to EN ISO 5211.

Actuator/control valve interface: Acc. to NAMUR or VDI/VDE 3845.

Actuator/signalling device interface: Acc. to VDI/VDE 3845 (NAMUR).

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Adapter ventila	Acc. to NAMUR Stainless steel
Material krogelnega ventila	1.4401, with ISO flange plate
Navoj	Rp 1
Pogonski material	Anodised aluminium
Premaz za krogelni ventil	PTFE
Premaz za pogon	NBR
Različica	double-acting
Priporočeni vodeni tlak [bar]	5.5
Max. vodeni tlak aktuatorja [bar]	10
DN	25
D [mm]	30.0
a/f [mm]	41
Max. obratovalni tlak [bar]	63
Max. delovna temperatura [°C]	70
Kot vrtenja [°]	90
L [mm]	90.0
A [mm]	133.0
B [mm]	157.0