

Datum: 30.04.2025



(slika je simbolična)

krogelni ventil robustnejša oblika, Z ročico, ročni, IT/ET, G/R 2

Kategorija: [Ball valve with hand lever, IT/ET](#)
Šifra: **103278RIE**

Kratek opis

Ball valve heavy duty design, Manual lever, IT/ET, nickel-plated brass, Operating temp. -20 °C to 130 °C, G/R 2, PN max. 63 bar

Applications: Compressed air, water, neutral and non-toxic gases, fuel oil (light distillate), fuel oil (heavy), lubricating oils, diesel oils.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Material navojev	Brass with a bare metal surface
Navoj	G/R 2
Ohišje	Nickel-plated brass
Ročica	Aluminium, painted black
Standardni navoj	G thread DIN EN ISO 228-1, R thread DIN EN 10226 (ISO 7-1)
Stebelno tesnilo	PTFE
F [mm]	21.0
E [mm]	25.5
DN	50
PN [bar]	63
a/f 1 [mm]	69
a/f 2 [mm]	70
B [mm]	115.5
Max. delovna temperatura [°C]	130
L [mm]	136.0
A [mm]	175.0