

Datum: 29.04.2025



(slika je simbolična)

## krogelni ventil s prirobnico, Pneumat. vklop, DN 20

Kategorija: [Stainless steel ball valves compact flange type](#)

Šifra: **103639RIE**

### Kratek opis

Compact flange ball valve, Pneumat. actuation drive, double-acting, Stainless steel, Operating temp. -10°C to 200°C, PN max 40 bar  
2-way ball valves compact flange type, full bore.  
Pneumatic actuators, double- or single acting version and integrated end-position feedback.

### Tehnične Specifikacije

|                             |                                                           |
|-----------------------------|-----------------------------------------------------------|
| Delovna temperatura         | -10 °C to 200 °C<br>(depending on the operating pressure) |
| Adapter ventila             | Acc. to NAMUR                                             |
| Material krogelnega ventila | Stainless steel 1.4408, with ISO flange                   |
| Pogonski material           | Anodised aluminium                                        |
| Premaz za krogelni ventil   | PTFE                                                      |
| Premaz za pogon             | NBR                                                       |
| Različica                   | double-acting                                             |
| Max. vodeni tlak [bar]      | 5.5                                                       |
| DN                          | 20                                                        |
| PN [bar]                    | 40                                                        |
| C [mm]                      | 44.0                                                      |
| E [mm]                      | 58.0                                                      |
| F [mm]                      | 61.5                                                      |
| Kot vrtenja [°]             | 90                                                        |
| D [mm]                      | 105.0                                                     |
| A [mm]                      | 116.0                                                     |
| B [mm]                      | 129.3                                                     |