

Datum: 15.12.2025



(slika je simbolična)

## krogelni ventil z podaljšanim navojem, IT/IT, Rp 1/2

Kategorija: [Ball valve, long-threaded type, IT/IT](#)

Šifra: **103237RIE**

### Kratek opis

Ball valve long thread design, IT/IT, nickel-plated brass,  
Operating temperature -15 °C to 90 °C, Rp 1/2, DN 15, PN  
max. 40 bar

Applications: Compressed air, water, non-toxic and non-  
corrosive gases, heating systems, agriculture.

### Tehnične Specifikacije

|                                  |                                    |
|----------------------------------|------------------------------------|
| Min. delovna<br>temperatura [°C] | -15                                |
| Krogelno tesnilo                 | PTFE                               |
| Krogla                           | Chrome-plated brass                |
| Material                         | Nickel-plated brass                |
| Material navojev                 | Brass with a bare metal<br>surface |
| Navoj                            | Rp 1/2                             |
| Ročica                           | Aluminium, painted black           |
| Standardni navoj                 | Thread acc. to ISO 7-1             |
| Stebelno tesnilo                 | HNBR / EPDM / PTFE                 |
| DN                               | 15                                 |
| Max. obratovalni tlak<br>[bar]   | 40                                 |
| B [mm]                           | 46.0                               |
| L [mm]                           | 61.0                               |
| A [mm]                           | 85.0                               |
| Max. delovna<br>temperatura [°C] | 90                                 |