

Datum: 17.12.2025



(slika je simbolična)

krogelni ventil z vgrajenim izpustom, nikljana medenina, G 3/4

Kategorija: [Ball valves with integrated strainer](#)

Šifra: **133555RIE**

Kratek opis

Ball valve, integrated strainer, nickel-plated brass,
Operating temp. -20°C to 100°C, G 3/4, DN 16, PN max. 30
bar, Mesh size 0.5

Space and cost saving combination made of ball valve and
dirt strainer in one.

Replaces the sequence of ball valve - dirt strainer - ball
valve and thus reduces installation time and costs.

The can be removed easily in locked, pressure released
status for cleaning.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass (CW617N)
Material navojev	Nickel-plated brass (CW617N)
Navoj	G 3/4
Ohišje	Nickel-plated brass (CW617N)
Ročica	Galvanised steel with plastic coating
Standardni navoj	G-thread acc. to DIN EN ISO 228-1
Stebelno tesnilo	NBR / FKM
Zaslon	Stainless steel, mesh size 0.5 mm
E [mm]	13.0
DN	16
a/f 2 [mm]	30
PN [bar]	30
a/f 1 [mm]	31
D [mm]	35.1
B [mm]	47.4
L [mm]	61.3
A [mm]	100.0
Max. delovna temperatura [°C]	100