

Datum: 30.04.2025



(slika je simbolična)

Manometer, CrNi jeklena varnostna verzija, G 1/2, 0-25 bar, Ø 100

Kategorija: [Pressure gauges \(CrNi steel type / safety housing\)](#)

Šifra: **102468RIE**

Kratek opis

Pressure gauge, CrNi steel, Safety design, Connection radial bottom, G 1/2, Goods class 1.0, Measurement range 0-25 bar, Ø 100

Bourdon-tube pressure gauge (safety housing), CrNi steel type, with solid baffle wall and blow-out (safety housing). Suitable for gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-40
Min. temperatura medija [°C]	-40
Material	CrNi steel
Material Prozessanschluss	CrNi steel
Položaj povezave	radial on bottom
Povezava	G 1/2
Prednje steklo	Laminated safety glass
Spodnja/Zgornja meja območja	Positive pressure
Stopnja rasti na območju skale - bar [bar]	0.5
Razred točnosti	1.0
Merilno območje max. bar	25
Max. sobna temperatura [°C]	60
Premjer [mm]	100
Max. temperatura medija [°C]	200
Vrsta	232.30