

Datum: 16.12.2025



(slika je simbolična)

## Manometer, robustna verzija, G 1/2, 0 - 100 bar, Ø 160

Kategorija: [Pressure gauge robust type, radial on bottom](#)

Šifra: **102051RIE**

### Kratek opis

Pressure gauge, robust design, Connection radial bottom, G 1/2, Goods class 1.0, Measurement range 0 - 100 bar, Ø 160  
Robust bourdon-tube pressure gauge.  
Suitable for gaseous or liquid media which do not corrode copper alloy,  
do not have high viscosity and do not crystallise.

### Tehnične Specifikacije

|                                            |                       |
|--------------------------------------------|-----------------------|
| Min. sobna temperatura [°C]                | -40                   |
| Min. temperatura medija [°C]               | -40                   |
| Material Prozessanschluss                  | Copper alloy          |
| Merilni element                            | CrNi steel            |
| Ohišje                                     | CrNi steel            |
| Položaj povezave                           | radial on bottom      |
| Povezava                                   | G 1/2                 |
| Prednje steklo                             | Flat instrument glass |
| Premikanje                                 | Copper alloy          |
| Spodnja/Zgornja meja območja               | Positive pressure     |
| Razred točnosti                            | 1.0                   |
| Stopnja rasti na območju skale - bar [bar] | 2                     |
| Max. sobna temperatura [°C]                | 60                    |
| Max. temperatura medija [°C]               | 80                    |
| Merilno območje max. bar                   | 100                   |
| Premier [mm]                               | 160                   |
| Vrsta                                      | 212.20                |