

Datum: 30.04.2025



MikroFilter»FUTURA«Kov. pos.0.01 µm, Vel.1, G 3/8, FA

(slika je simbolična)

Kategorija: [Microfilter with metal bowl and sight glass](#)

Šifra: **156577RIE**

Kratek opis

Microfilter »FUTURA«, Metal container and viewing tube, 0.01 µm, Size 1, G 3/8, 1.5-16 bar, Temp. -10 °C to 50 °C, Fully-automatic

Micro-filters in modern design for compliance with strict compressed air purity requirements.

Micro-filters are used to separate solid oil, water and solid impurities as small as 0.01 µm from compressed air and gases.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Borosilicate glass fibre
Ločevanje prahu	> 0.01 µm 99.999 %
Merjenje pretoka	At P ₂ = 6 bar and pressure drop Δ _p = 0.1 bar
Navoj	G 3/8
Odtok kondenzata	Fully-automatic
Ohišje	PA66 GF60
Posoda	Metal container with viewing tube
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Vsebnost olja v ostanku [mg/m ³]	< 0.01
Rang filtra [µm]	0.01
Velikost	1
Min. vhodni tlak [bar]	1.5
Max. vhodni tlak [bar]	16
C [mm]	39.5
Max. temperaturno območje [°C]	50
A [mm]	52.0
B [mm]	186.5
Pretok [l/min]	350