

Datum: 30.04.2025



(slika je simbolična)

## **MikroFilter »multifix-mali«PC zbir.0.01 µmVel. 0G 1/8**

Kategorija: [Microfilter with polycarbonate bowl](#)

Šifra: **100372RIE**

### **Kratek opis**

Microfilter »multifix-mini« with PC container, 0.01 µm, Size 0, G 1/8, Input pressure max. 16 bar, Med. / ambient temp. max. 60 °C  
For filtering out solid impurities larger than 0.01 µm.

### **Tehnične Specifikacije**

|                                              |                                                         |
|----------------------------------------------|---------------------------------------------------------|
| Element filtra                               | Borosilicate-POM                                        |
| Merjenje pretoka                             | At $P_1 = 6$ bar and pressure drop $\Delta_p = 0.1$ bar |
| Navoj                                        | G 1/8                                                   |
| Odtok kondenzata                             | Semi-automatic                                          |
| Ohišje                                       | Die-cast zinc                                           |
| Posoda                                       | Polycarbonate container                                 |
| Serija                                       | multifix-mini                                           |
| Tesnilo                                      | NBR                                                     |
| Rang filtra [µm]                             | 0.01                                                    |
| Vsebnost olja v ostanku [mg/m <sup>3</sup> ] | 0.01                                                    |
| DN                                           | 5                                                       |
| C [mm]                                       | 12.3                                                    |
| Max. vhodni tlak [bar]                       | 16                                                      |
| A [mm]                                       | 40.0                                                    |
| Max. sobna temperatura [°C]                  | 60                                                      |
| Max. temperatura medija [°C]                 | 60                                                      |
| Učinkovitost [%]                             | 99.999                                                  |
| D [mm]                                       | 102.5                                                   |
| B [mm]                                       | 114.8                                                   |
| Pretok [l/min]                               | 230                                                     |