

Datum: 30.04.2025



(slika je simbolična)

MikroFilter »variobloc«Zašč. kletka0.01 µmVel. 2G 3/4

Kategorija: [Microfilter with polycarbonate bowl and bowl guard](#)

Šifra: **124814RIE**

Kratek opis

Microfilter »variobloc« with PC container and protective cage, 0.01 µm, Size 2, G 3/4, Input pressure max. 16 bar, Temp. max. 50°C

Borosilicate filter for all applications where compliance with strict compressed air purity requirements is vital.

As the second stage downstream of the standard filter, the micro-filter removes 99.999 % of even the finest remaining particles from water, oil and dirt with practically zero residues (filter rating: 0.01 µm).

Tehnične Specifikacije

Kakovost zraka po ISO 8573.1	Class 1 dirt, class 1 oil
Merjenje pretoka	At $P_1 = 7$ bar and pressure drop $\Delta p = 0,1$ bar
Navoj	G 3/4
Posoda	Polycarbonate container with protective cage
Serijska	variobloc
Rang filtra [µm]	0.01
Velikost	2
Max. vhodni tlak [bar]	16
C [mm]	26.0
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	50
A [mm]	70.0
Učinkovitost [%]	99.999
B [mm]	202.0
Pretok [l/min]	1100