

Datum: 30.04.2025



(slika je simbolična)

MikroFilter z diferencialnim manometrom, 0.01 µm, G 1

Kategorija: [Microfilter with differential pressure gauge](#)

Šifra: **101564RIE**

Kratek opis

Microfilter with differential pressure gauge, 0.01 µm, G 1,
Input pressure 4 - 12 bar, Medium / ambient temperature 5
°C to 60 °C

Ideal for filtering out aerosols and solid impurities larger
than 0.01 µm.

Micro-filters should always be used in conjunction with a
pre-filter.

Tehnične Specifikacije

Element filtra	Borosilicate (with glass-fibre material and foam plastic)
Merjenje pretoka	At P ₁ = 6 bar and pressure drop Δ _p = 1.5%
Navoj	G 1
Ohišje	Aluminium
Posoda filtra	Aluminium
Rang filtra [µm]	0.01
Max. označeni razpon diferencialnega manometra [bar]	2
Min. vhodni tlak [bar]	4
Min. sobna temperatura [°C]	5
Min. temperatura medija [°C]	5
Max. vhodni tlak [bar]	12
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
C [mm]	72.0
Učinkovitost [%]	99.9999
A [mm]	118.0
B2 [mm]	420.0
D [mm]	458.0
B1 [mm]	517.5
Pretok [l/min]	4080