

Datum: 15.12.2025



(slika je simbolična)

Mikrometrski manometer, priklop spodaj, G 1/2, 0-250 bar, Ø 160

Kategorija: [Precision pressure gauges](#)

Šifra: **102576RIE**

Kratek opis

Micrometre pressure gauge, Connection radial bottom, G 1/2, Goods class 0.6, Measurement range 0-250 bar, Ø 160 Bourdon-tube pressure gauge for precision measurements. Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Material Prozessanschluss	Copper alloy
Merilni element	CrNi steel
Ohišje	CrNi steel
Okvir	CrNi steel
Položaj povezave	radial on bottom
Povezava	G 1/2
Prednje steklo	Flat instrument glass
Premikanje	Copper alloy
Spodnja/Zgornja meja območja	Positive pressure
Razred točnosti	0.6
Stopnja rasti na območju skale - bar [bar]	2
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	80
Premier [mm]	160
Merilno območje max. bar	250
Vrsta	312.20