

Datum: 16.12.2025



(slika je simbolična)

Naoljevalnik »G«PC zbir.Zašč. kletkaVel. 300G 3/8

Kategorija: [Oil-mist lubricator with PC bowl, bowl guard](#)

Šifra: **116444RIE**

Kratek opis

Mist oiler »G«, PC container, Protective cage, Mounting bracket, Size 300, G 3/8, Input pres. max. 10 bar, Working pres. 0.5-9 bar
Proportional lubricators, oil can be filled under pressure.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p =$ 1 bar
Navoj	G 3/8
Ohišje	Die-cast aluminium
Posoda	Polycarbonate container with protective cage
Serija	G
Tesnilo	NBR
Vidna kupola	Brass/POM
Vzmet pokrova motorja	POM
Min. delovni tlak [bar]	0.5
Max. delovni tlak [bar]	9
Max. vhodni tlak [bar]	10
C [mm]	44.0
A [mm]	51.0
Max. sobna temperatura [°C]	70
Max. temperatura medija [°C]	70
D [mm]	125.0
B [mm]	169.0
Velikost	300
Pretok [l/min]	2650