

Datum: 15.12.2025



(slika je simbolična)

Naoljevalnik »variobloc«PC zbir.Protec. cageVel.1,G 3/8

Kategorija: [Oil-mist lubricator with PC bowl and bowl guard](#)

Šifra: **124817RIE**

Kratek opis

Mist oiler »variobloc«, PC container, protective cage, Size 1, G 3/8, Input pressure max. 16 bar, Medium / ambient temp. max. 50°C

Proportional lubricators, oil can be filled under pressure.

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 3/8
Ohišje	Die-cast zinc
Posoda	Polycarbonate container with protective cage
Razred olja	CL 32 acc. to DIN 51517-ISO VG 32
Serijska	variobloc
Tesnilo	NBR
Vidna kupola	PA
Velikost	1
Max. vhodni tlak [bar]	16
A [mm]	48.0
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	50
C [mm]	52.0
B [mm]	171.0
Pretok [l/min]	4400