

Datum: 15.12.2025



(slika je simbolična)

Naoljevalnik »variobloc« s kovinsko posodo, Velikost 1, G 1/4

Kategorija: [Oil-mist lubricator, metal bowl, incl. sight glass](#)

Šifra: **125335RIE**

Kratek opis

Mist oiler »variobloc« with metal container incl. viewing tube, Size 1, G 1/4, Input pressure max. 20 bar, Medium temp. max. 80°C

Proportional lubricators, oil can be filled under pressure. Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/4
Ohišje	Die-cast zinc
Posoda	Metal container with viewing tube
Razred olja	CL 32 acc. to DIN 51517-ISO VG 32
Serijska	variobloc
Tesnilo	NBR
Vidna kupola	PA
Velikost	1
Max. vhodni tlak [bar]	20
A [mm]	48.0
C [mm]	60.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	80
B [mm]	180.0
Pretok [l/min]	3400