

Datum: 16.12.2025



(slika je simbolična)

Naoljevalnik »variobloc« z PC zbiralnik, Velikost 2, G 1

Kategorija: [Oil-mist lubricator with polycarbonate bowl](#)

Šifra: **100707RIE**

Kratek opis

Mist oiler »variobloc« with polycarbonate container, Size 2, G 1, Input pressure max. 16 bar, Medium / ambient temp. max. 50 °C

Proportional lubricators, oil can be filled under pressure.

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1
Ohišje	Die-cast zinc
Posoda	Polycarbonate container
Razred olja	CL 32 acc. to DIN 51517-ISO VG 32
Serijska	variobloc
Tesnilo	NBR
Vidna kupola	PA
Velikost	2
Max. vhodni tlak [bar]	16
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	50
C [mm]	57.0
A [mm]	124.0
B [mm]	224.0
Pretok [l/min]	7500