

Datum: 16.12.2025



(slika je simbolična)

Natančen Tlačni reg. »multifix« Vel. 3G 1/2, 0.2-6 barKategorija: [Precision pressure regulators](#)Šifra: **100458RIE****Kratek opis**

Precision pressure regulator »multifix«, incl. pressure gauge,
Size 3, G 1/2, Input pressure max. 16 bar, Control range
0.2-6 bar

Diaphragm pressure regulators, independent of inlet
pressure, with self-relieving design
and very high flow rate.

The pressure setting can be locked by pushing the button
down.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/2
Ohišje	Die-cast zinc
Poraba zraka	Yes
Serijska	multifix
Tesnilo	NBR
Vzmet pokrova motorja	POM-brass
Min. krmilno območje [bar]	0.2
Max. notranja poraba zraka	2.6 l/min (depending on secondary pressure)
Velikost	3
Max. krmilno območje [bar]	6
Zaslona manometra max. [bar]	10
DN	15
Max. vhodni tlak [bar]	16
D [mm]	35.1
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
A [mm]	68.8
C [mm]	99.0
B [mm]	134.1
Pretok [l/min]	7600