

Datum: 30.04.2025



(slika je simbolična)

## Natančni filter regulatorji, Brez barvnih kovin, 0.1-3 bar

Kategorija: [Precision filter regulators](#)

Šifra: **101218RIE**

### Kratek opis

Precision filter regulator without pressure gauge, Free of non-ferrous metals, G 1/4, Control range 0.1 - 3 bar  
Diaphragm pressure regulators containing no non-ferrous metals, with secondary venting, combined with a centrifugal separator for applications requiring an extremely accurate working pressure.

### Tehnične Specifikacije

|                              |                                                          |
|------------------------------|----------------------------------------------------------|
| Navoj                        | G 1/4                                                    |
| Navoj manometra              | G 1/4                                                    |
| Ohišje                       | Die-cast zinc                                            |
| Poraba zraka                 | Yes                                                      |
| Srednje                      | Micro-filtered, unoiled compressed air (0.01 µm)         |
| Tesnilo                      | NBR                                                      |
| Min. krmilno območje [bar]   | 0.1                                                      |
| Max. notranja poraba zraka   | 0.2 l/min, depending on input pressure and control range |
| Max. krmilno območje [bar]   | 3                                                        |
| Rang filtra [µm]             | 10                                                       |
| Max. vhodni tlak [bar]       | 16                                                       |
| A [mm]                       | 60.0                                                     |
| Max. sobna temperatura [°C]  | 60                                                       |
| Max. temperatura medija [°C] | 60                                                       |
| D [mm]                       | 96.0                                                     |
| C [mm]                       | 120.0                                                    |
| B [mm]                       | 216.0                                                    |
| Pretok                       | 750 l/min                                                |