

Datum: 16.12.2025



(slika je simbolična)

## Nav. klik klak M5 , zun. Ø 3

Kategorija: [Push-in plug, parallel male thread with O-ring](#)

Šifra: **108699RIE**

## Kratek opis

Thread plug nipple »click-clock«, M5 o., for hose exterior Ø 3 mm, Working pressure -0.99 to 16 bar, nickel-plated brass  
By combining these parts with unions, union elbows and union tees, you can obtain all essential connecting variants and simultaneously reduce your warehousing costs.  
Only recommended for use in combination with quick-connect fittings of the "click-clock" series.  
The suitability test for use with other series is the responsibility of the user.

## Tehnične Specifikacije

|                               |                     |
|-------------------------------|---------------------|
| Min. delovna temperatura [°C] | -20                 |
| Min. delovni tlak [bar]       | -0.99               |
| Material                      | Nickel-plated brass |
| Navoj                         | M5                  |
| Serija                        | click-clock         |
| Vpenjalni obroč               | Stainless steel     |
| Za cevi O.D. [mm]             | 3                   |
| a/f [mm]                      | 5                   |
| Max. delovni tlak [bar]       | 16                  |
| L1 [mm]                       | 16.8                |
| Max. delovna temperatura [°C] | 80                  |