

Datum: 30.04.2025

Davčna št.: SI 56119488

Telefon: 01 500 14 42

E-mail: info@podjetje-trg.si

WWW: www.karchertest.staging.digitalist.si



(slika je simbolična)

Nav. priklj. 330, N.N./N.N.Rp/Rp 1/4,č. kovanlit. ž.

Kategorija: [Union 330, flat seat, female/female, with NBR-seal](#)

Šifra: **113160RIE**

Kratek opis

Fitting 330, flat sealing, IT/IT, Rp/Rp 1/4, NBR seal,
Operating temp. -20°C to 200°C, black malleable cast iron,
Hot-dip galva.

"

Maximum temperature and maximum operating pressure
should not occur at the same time!

Acc. to DIN EN 10242 (formerly DIN 2950)

The classic - and the most popular - screw fitting series for
pipe construction.

These fittings are characterized by their high mechanical
strength and surface quality to DIN 2444.

They are completely coated with a layer of pure zinc and are
therefore suitable for drinking water

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Material	Black malleable iron B350-10, design symbol A
Navoj	Rp/Rp 1/4
Površina	Hot dip galvanised
Standardni navoj	acc. ISO 7-1
Max. temperaturno območje [°C]	200