

Datum: 29.04.2025



(slika je simbolična)

Okrogli cilinder, delujoč v dveh smereh, bat Ø 20, hod 125, G 1/8

Kategorija: [Round cylinders, double acting, with magnet](#)
Šifra: **105783RIE**

Kratek opis

Round cylinder, ISO 6432, double-acting, Magnet, Piston Ø 20, Stroke 125, G 1/8, Working pressure max. 10 bar, Temp. -10°C to 80°C

Single and double-acting cylinders, with magnetic piston. Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Bat	Synthetic (acetal) resin
Batnica	C45 steel, hard chrome-plated
Cushioning	non-cushioned
Ffunkcija	double-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Navoj na batnici	M8
Oblika	Flanged joint between stainless steel barrel and heads
Ovoj	Stainless steel 1.4301
Povezava	G 1/8
Standard	acc. to ISO 6432
Tesnilo	NBR
Min. nastavljeni tlak [bar]	0.6
Max. delovni tlak [bar]	10
Bat Ø [mm]	20
Max. temperaturno območje [°C]	80
Stroke [mm]	125