

Datum: 17.12.2025



(slika je simbolična)

## Okrogli cilinder, delujoč v dveh smereh, bat Ø 50, hod 50, G 1/4

Kategorija: [Round cylinders, double acting, with magnet](#)  
Šifra: **105870RIE**

### Kratek opis

Round cylinder, double-acting, with magnet, Piston Ø 50, Stroke 50, G 1/4, Working pressure max. 10 bar, Temp. -10 °C to 80 °C

Version with magnetic piston.

Suitable for filtered (50 µm), unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

### Tehnične Specifikacije

|                                |                                                        |
|--------------------------------|--------------------------------------------------------|
| Min. temperaturno območje [°C] | -10                                                    |
| Bat                            | Technopolymer                                          |
| Batnica                        | C45 steel, hard chrome-plated                          |
| Cushioning                     | non-cushioned                                          |
| Ffunkcija                      | double-acting                                          |
| Gewinde Kolbenstange           | male piston rod                                        |
| Magnet                         | with magnet                                            |
| Navoj na batnici               | M16x1.5                                                |
| Oblika                         | Screwed joint between stainless steel barrel and heads |
| Ovoj                           | Anodised aluminium                                     |
| Povezava                       | G 1/4                                                  |
| Tesnilo                        | NBR                                                    |
| Min. nastavljeni tlak [bar]    | 0.3                                                    |
| Max. delovni tlak [bar]        | 10                                                     |
| Bat Ø [mm]                     | 50                                                     |
| Stroke [mm]                    | 50                                                     |
| Max. temperaturno območje [°C] | 80                                                     |