

Datum: 30.04.2025



(slika je simbolična)

## Okrogli cilinder, enosmerni, bat Ø 25, hod 10, G 1/8

Kategorija: [Round cylinders, single-acting, with magnet](#)

Šifra: **105837RIE**

### Kratek opis

Round cylinder, ISO 6432, single-acting, Magnet, Piston Ø 25, Stroke 10, G 1/8, Working pressure max. 10 bar, Temp. -10°C to 80°C

Single and double-acting cylinders, with magnetic piston. Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

### Tehnične Specifikacije

|                                |                                                        |
|--------------------------------|--------------------------------------------------------|
| Min. temperaturno območje [°C] | -10                                                    |
| Bat                            | Synthetic (acetal) resin                               |
| Batnica                        | C45 steel, hard chrome-plated                          |
| Cushioning                     | non-cushioned                                          |
| Ffunkcija                      | single-acting                                          |
| Gewinde Kolbenstange           | male piston rod                                        |
| Magnet                         | with magnet                                            |
| Navoj na batnici               | M10x1.25                                               |
| Oblika                         | Flanged joint between stainless steel barrel and heads |
| Ovoj                           | Stainless steel 1.4301                                 |
| Povezava                       | G 1/8                                                  |
| Standard                       | acc. to ISO 6432                                       |
| Starting position              | pressureless in the retracted position                 |
| Tesnilo                        | NBR                                                    |
| Min. nastavljeni tlak [bar]    | 0.6                                                    |
| Max. delovni tlak [bar]        | 10                                                     |
| Stroke [mm]                    | 10                                                     |
| Bat Ø [mm]                     | 25                                                     |
| Max. temperaturno območje [°C] | 80                                                     |