

Datum: 15.12.2025



(slika je simbolična)

## Okrogli cilinder TP delujoč v dveh smerehbat Ø 25hod 100G 1/8

Kategorija: [Round cylinders TP](#)

Šifra: **105724RIE**

### Kratek opis

Round cylinder TP (ISO 6432) double-acting, Piston Ø 25, Stroke 100, G 1/8, Working pressure max. 10 bar, Temp. -10 °C to 60 °C

Inexpensive standard version with aluminum pipe and magnet piston.

Suitable for filtered (50 µm), unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

### Tehnične Specifikacije

|                                |                                               |
|--------------------------------|-----------------------------------------------|
| Min. temperaturno območje [°C] | -10                                           |
| Batnica                        | C45 steel, hard chrome-plated                 |
| Cushioning                     | non-cushioned                                 |
| Dno                            | Technopolymer                                 |
| ET batnice                     | M10x1.25                                      |
| Ffunkcija                      | double-acting                                 |
| Gewinde Kolbenstange           | male piston rod                               |
| Glava                          | Technopolymer                                 |
| Magnet                         | with magnet                                   |
| Oblika                         | Connection: Aluminium pipe / end caps flanged |
| Ovoj                           | Aluminium alloy, anodised                     |
| Povezava                       | G 1/8                                         |
| Puša                           | Technopolymer                                 |
| Serijska                       | TP series                                     |
| Standard                       | acc. to ISO 6432                              |
| Tesnilo batnice                | PU                                            |
| Min. nastavljeni tlak [bar]    | 0.6                                           |
| Max. delovni tlak [bar]        | 10                                            |
| Bat Ø [mm]                     | 25                                            |
| Max. temperaturno območje [°C] | 60                                            |
| Stroke [mm]                    | 100                                           |